



### Characteristics

External dimensions : 400 X 835 X 900  
 Stainless steel top 18.10 planetary planetary brushed finish  
 Top thickness : 3 mm  
 body 1 mm in planetary brushed stainless steel  
 Structure : 2 mm in stainless steel  
 Stand with composite feet of 150 adjustable in height  
 folded front edge radius 20 mm  
 Back edge forming a chimney cover  
 Front without any visible screw

### Top


Net 20L stainless steel tank thickness 1.5mm  
 Power : 20 kW  
 Efficiency: 30-35 kg/h 6x6 frozen french fries  
 Thermostat 180°C positive security 220°C  
 Heating by 7 submerged nozzles and torch burners  
 Electric ignition  
 Security by thermocouple with pilotlight  
 Draining by 1/4 turn tap diam 20/27  
 1 stainless steel basket dimension : 360x285x135

### Options :

1/2 basket 360x140x135 pack of 2 (X082033)  
 large basket (360x285x135) (X291005)

### Base unit

Construction in stainless steel 18.10  
 Structure 2 mm  
 body 1 mm  
 External dimensions : 400x724x650  
 Front without any visible screw  
 Double skin door



## GAS



Gas power : 20kW

Gas connection : 15/21 MALE TAPERING

Gas appliances complying with standard NF EN 203.EN 437

Gas Directive 2009/142/EC

## ELECTRIC



Electric power : 0.25kW

Elec Réserve : INTERNAL TERMINAL BOARD - Elec fitting : 230V SINGLE

Electrical devices standard to the norm EN 60-335