

# Fryer Smart 130

**Production: 130 kg/h**

**Strengths: Complete automation, filtration and automatic oil refill and level system.**



- Capacity 2x23 litres.
- Electric power 2x28 kW.
- 30/10 top thickness - peripheral gutter.
- Planetary brushed finish.
- Safety thermostat and electromechanical temperature regulation independent for each tank.
- 4 independent automatic basket liftings with timer and programmable recipes.
- 4x1/2 baskets of 360x160x135.
- Oil pre-heating: 180°C in 6min.
- Automatic filtering process with warning system associated to various cycles.
- Removable filter on wheels.
- Continuous automatic oil level system.
- Cleaning program.
- The fryer can be cantilevered.

## **IMPORTANT: Speed**

- Temperature rise time: 180°C in 6 minutes (cold start).
- Draining time filtration and automatic oil refill and on level in only 4 minutes.

Oblong heating elements, tilting system for cleaning with heating safety cut and locking system of the heating elements in lifted position.

**Front 1000  
Depth: 836 Celtic - 925 Armen**



**CAPIC**  
France 1955 ★★★★★

5 rue Haroun Tazieff - CS 35007 - 29556 QUIMPER Cedex 9 - France  
Tel. +33 (0)2 98 64 77 00 - Fax +33 (0)2 98 52 06 47 - email : [capic@capic-fr.com](mailto:capic@capic-fr.com) - [www.capic-fr.com](http://www.capic-fr.com)

The equipments presented in this documentation are manufactured in Brittany-France by CAPIC.  
Photos, features and drawings are just given for your information and are not contractual.



# Fryer Smart 130

Complete automation, filtration and automatic oil refill and level system.

## Characteristics

- Dimensions Celtic range: 1000x836x900/930
- Dimensions Armen range : 1000x925x900/930
- 18.10 stainless steel top.
- Top thickness 30/10.
- 10/10 stainless steel covering panels.
- 20/10 stainless steel structure.
- Adjustable feet height 150 with composite jack.
- Rounded front edge (radius : 20°).
- Rear edge forming splashguard on vent hood.
- Front without apparent screws.

## Top

- 2 stainless steel tanks 23 litres.
- Electrical power : 2x28kW.
- Safety thermostat and independent electromechanical temperature regulation for each tank.
- 4 independent automatic basket liftings with timer and programmable recipes.
- Automatic filtering process with warning system associated to various cycles.
- Filtration and automatic oil refill with level system and accessories.
- Stainless steel oblong heating elements.

## Base

- Lined door.
- Removable filter on wheels. Level sensor for checking the amount of oil.

